

EcoTimber HealthyBond™ Adhesive

For Glue-down Applications of Wood and Bamboo Flooring

FEATURES

- High solids for superior coverage - up to 240 square feet per 4-gallon bucket
- Easy to spread, good early strength for immediate grab
- Tenacious but resilient bond, waterproof, freeze-thaw stable
- For use above, on or below grade
- Resin-based formula outperforms urethanes
- Adheres to hardwood, Bamboo, cork, plywood, concrete, vinyl, particleboard, and terrazzo (Not recommended for True Teak)

ENVIRONMENTAL BENEFITS

- GreenGuard® Indoor Air Quality Certified
- Meets all federal, state & local indoor air quality regulations
- Solvent-free, isocyanate-free, virtually VOC-free (only 7g per liter)
- Contains no hazardous chemicals (per OSHA SFR 1910.1200)
- Qualifies for LEED® Credit: EQ 4.1 | Low Emitting Materials



EcoTimber Floating Floor Pad

For Use Under Engineered Hardwood and Engineered Bamboo Flooring



FEATURES

- Suitable for use over all types of subfloors
- Insulates cold floors
- Random air-laid capillary construction cushions floor, smooths out subfloor imperfections
- Pre-attached vapor barrier helps prevent water damage
- Absorbent synthetic fibers disperse moisture away from wettest areas

ENVIRONMENTAL BENEFITS

- EPA-registered anti-microbial agent and high-temperature manufacture inhibit bacterial, fungal & dust mite growth
- Minimum 92% post-industrial recycled content
- No detectable formaldehyde emissions
- Qualifies for LEED® Credits: MR 4.1 and 4.2 | Recycled Content

Please visit www.ecotimber.com for full technical specifications and installation instructions